

Description

Double-shielded Drop Coaxial Cable, for digital reception - 75 Ohm

Cable for digital reception (Screening attenuation - Class A+)

**Data Sheet****DG113**

Ø	1,13	4,80	4,90	5,30	6,60
	(Cu)	(PEG)	(Al/Pet/Al)	(CuSn)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EN50117-9-2

CEI-UNEL 36762

Reaction to Fire

EN50575

Application

DOCSIS 3.1 (Data Over Coax System), Satellite Internet (VSAT)

8K-UHD

Indoor Installation

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 ± 0,10	mm
Aluminum/Polyester/Aluminum tape longitudinally overlapped	(Al/Pet/Al)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		72	%
Diameter over Braid		Ø 5,30	mm
Outer sheath of Polyvinylchloride - white - lead-free	(PVC)	Ø 6,60 ± 0,10	mm

Printed each meter by blue ink-jet :

CAVEL DG 113 MADE IN ITALY 75 Ohm Euroclass Eca SA Class A+ EN50117-9-2 CEI-UNEL 36762 C-4 (U0 = 400V) ULTRA HD / 8K gggaa(n) m

(gggaan=batch number m=meter marking)

Physical data

Weight of copper conductors	19,20	kg/km
Total weight of cable	43,17	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Maximum cable pulling strength	150	N
Minimum installation temperature	-5	°C
Operating temperature	-20 / +70	°C

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

09/03/2026

Responsible

A. Bergaglio

Description

Double-shielded Drop Coaxial Cable, for digital reception - 75 Ohm

Cable for digital reception (Screening attenuation - Class A+)

**Data Sheet****DG113****Electrical data**

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		18	Ohm/km
Outer conductor resistance		13,90	Ohm/km
Loop resistance		31,90	Ohm/km
Sheat Insulation voltage (spark test)		2,50	kV
Maximum current (I _{eff})		8	A

Structural return loss (SRL)

5 - 470 MHz	>30 dB
470 - 1000 MHz	>28 dB
1000 - 2000 MHz	>26 dB
2000 - 3000 MHz	>22 dB

Screening Attenuation (SA)

SA-Class A+

Transfer Impedance (Z_t)

30 - 1000 MHz	>95 dB
1000 - 2000 MHz	>90 dB
2000 - 3000 MHz	>80 dB

5 - 30 MHz

< 5 mOhm/m

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,60	690	15,10
10	2,30	1000	18,50
30	3,20	1750	24,90
50	4,10	2150	27,90
200	8,00	2400	29,60
300	9,80	3000	33,40
470	12,40		

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date**09/03/2026****Responsible****A. Bergaglio**

Description Double-shielded Drop Coaxial Cable, for digital reception - 75 Ohm Cable for digital reception (Screening attenuation - Class A+)			Data Sheet DG113
Connectors			
BNCC703	Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm		
C75-5L	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation		
CCFM75GI	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation		
CS00	Stripper for Drop Cables, Standard cables from 5 to 7 mm, Tools -		
DR01	Adapter, Nut and Washer, for INDOOR installation		
F703	Series F Crimp, F Crimp, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm		
F81-HQ	Adapter, F Adapter FF, for INDOOR installation		
F90	Series F Crimp, F Crimp, for INDOOR installation		
FA703	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm		
FC7.0QM	Series F Compression, Quick Mount, for OUTDOOR installation		
FC703	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass - 30,0 mm x 12,0 mm		
FC703C	Series F Compression, F Compression, for OUTDOOR installation		
FCEM7.0C	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass		
FCPO5.1C	Series F Compression, Ø 5,1 Push-On, for OUTDOOR installation, nitin-plated brass		
FM-FF90	Adapter, FM - FF 90°, for INDOOR installation		
FR703	Series F Crimp, F crimp, "Rapid", for INDOOR installation		
IECF5.1C	Series IEC (toolless), female, no tool, for INDOOR installation		
IECF90C	Series IEC (toolless), Ø 5,1 90° female, for INDOOR installation		
IECF703	Serie IEC Compression, female, no tool, for OUTDOOR installation		
IECM5.1C	Series IEC (toolless), male, no tool, for INDOOR installation		
IECM90C	Series IEC (toolless), Ø 5,1 90° male, for INDOOR installation		
IECM703	Serie IEC Compression, male, for OUTDOOR installation		
LTE790	Indoor Fittings, Filter, for INDOOR installation		
MM-F703	Adapter, F Adapter MM, for INDOOR installation		
MM-FR703	Adapter, F Adapter MM, for INDOOR installation		
SAT2VS	Indoor Fittings, F SAT 2-way Splitter, for INDOOR installation		
TV2VS	Indoor Fittings, IEC TV 2-way Splitter, for INDOOR installation		
ITALIANA CONDUTTORI s.r.l. Viale Zanotti 90 I - 27027 Gropello Cairoli Tel +39-382.815150 Fax +39-0382.814212		Date 09/03/2026	Responsible A. Bergaglio