

Description

Double-shielded Drop Coaxial Cable, for digital reception - 75 Ohm

Cable for digital reception (Screening attenuation - Class A+)

**Data Sheet****DG113PE**

Ø	1,13	4,80	4,90	5,30	6,60
	(Cu)	(PEG)	(Al/Pet/Al)	(CuSn)	(PE)

Class CPR acc. to UE 305/2011 (DoP)

Fca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EN50117-10-2

CEI-UNEL 36762

Reaction to Fire

EN50575

Application

DOCSIS 3.1 (Data Over Coax System)

8K-UHD

Exterior and Underground Installation

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 ± 0,10	mm
Outer Aluminum/Polyester/Aluminum tape longitudinally overlapped	(Al/Pet/Al)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		72	%
Diameter over Braid		Ø 5,30	mm
Outer sheath of Polyethylene - black (RAL 9011) - with carbonblack	(PE)	Ø 6,60 ± 0,10	mm
Printed each meter by yellow ink-jet :			

CAVEL DG 113 PE MADE IN ITALY 75 Ohm Euroclass Fca EN50117-10-2 SA Class A+ CEI-UNEL 36762
C-4 (U0 = 400V) ULTRA HD / 8K gggaan m

(gggaan=batch number m=meter marking)

Physical data

Weight of copper conductors	19,20	kg/km
Total weight of cable	38,90	kg/km
Minimum bending radius (single/repetead bending)	35/70	mm
Maximum cable pulling strength	150	N
Minimum installation temperature	-5	°C
Operating temperature	-25 / +80	°C

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date

09/03/2026

Responsible

A. Bergaglio

Description				Data Sheet
Double-shielded Drop Coaxial Cable, for digital reception - 75 Ohm				DG113PE
Cable for digital reception (Screening attenuation - Class A+)				
Electrical data				
Characteristic impedance	200 MHz	75 ± 3	Ohm	
Capacitance (@1kHz)		52 ± 2	pF/m	
Velocity Ratio		85 %		
Inner conductor resistance		18	Ohm/km	
Outer conductor resistance		13,90	Ohm/km	
Loop resistance		31,90	Ohm/km	
Sheat Insulation voltage (spark test)		2,50	kV	
Maximum current (Ieff)		8	A	
Structural return loss (SRL)				
5 - 470 MHz	>30 dB			
470 - 1000 MHz	>28 dB			
1000 - 2000 MHz	>26 dB			
2000 - 3000 MHz	>22 dB			
Screening Attenuation (SA)	SA-Class A+	Transfer Impedance (Zt)		
30 - 1000 MHz	>95 dB	5 - 30 MHz	< 5 mΩ/m	
1000 - 2000 MHz	>90dB			
2000 - 3000 MHz	>80 dB			
Attenuation (at 20°C)				
Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]	
5	1,60	690	15,10	
10	2,30	1000	18,50	
30	3,20	1750	25,20	
50	4,10	2150	27,90	
200	8,00	2400	29,70	
300	9,80	3000	33,40	
470	12,40			
Connectors				
BNCC703	Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm			
CS00	Stripper for Drop Cables, Standard cables from 5 to 7 mm, Tools -			
CS17VP	Stripper for Drop Cables, for 17PATC, Tools -			
FC7.0QM	Series F Compression, Quick Mount, for OUTDOOR installation			
FC703	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass - 30,0 mm x 12,0 mm			
FC703C	Series F Compression, F Compression, for OUTDOOR installation			
FC703C	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass			
FCPO5.1C	Series F Compression, Ø 5,1 Push-On, for OUTDOOR installation, nitin-plated brass			
IECF5.1C	Series IEC (toolless), female, no tool, for INDOOR installation			
IECF703	Serie IEC Compression, female, no tool, for OUTDOOR installation			
IECM5.1C	Series IEC (toolless), male, no tool, for INDOOR installation			
IECM703	Serie IEC Compression, male, for OUTDOOR installation			
ITALIANA CONDUTTORI s.r.l.		Date	Responsible	
Viale Zanotti 90 I - 27027 Gropello Cairoli		09/03/2026	A. Bergaglio	
Tel +39-382.815150 Fax +39-0382.814212				